

What is claimed is:

1. A two-shaft rotary safety cutter, comprising essentially of:

a worktable board set, comprising a worktable board for placing a paper to be cut; a fixed blade connected to the top edge of said worktable board and having
5 a cant edge; and four rubber feet disposed under the corners of said worktable board;

a side guide set, comprising a side guide fixed to one side of said worktable board; a depth guide having thereon a bolt hole for allowing said depth guide to be movably connected to said side guide; and a depth guide knob bolted in said
10 bolt hole of said depth guide;

a bracket set, comprising a right bracket pivotally coupled to the right side of said worktable board; a left bracket pivotally coupled to the left side of said worktable board; and two carriage sliding shafts, wherein both shaft ends of said carriage sliding shafts are coupled to the corresponding apertures on said right
15 bracket and said left bracket; and

a blade carriage set, comprising a carriage movably coupled to said carriage sliding shafts and sliding along said fixed blade at the top edge of said worktable board back and forth; a blade provided on said carriage and sliding along said fixed blade at the top edge of said worktable board as said carriage slides along
20 said carriage sliding shafts; and a rubble element provided on said carriage, being concentric with said blade, and rolling on a paper holder as said carriage slides along the carriage sliding shafts;

wherein said paper holder is flat and provided with a strip-shaped safety rim, and is provided with a blade accommodating slot at an appropriate location
25 above said fixed blade, wherein both sides of said paper holder is coupled to said bracket set, and said safety rim of said paper holder is parallel with and protruded

from the top edge of said worktable board; wherein both sides of said paper holder is coupled to said right bracket and said left bracket of said bracket set, and said safety rim parallel with and protruded from the top edge of said worktable board provides a safety guard device for the cant edge of said fixed blade.

5 2. The two-shaft rotary safety cutter according to claim 1, wherein said safety rim is integrally formed with said paper holder onto said bracket set.

3. The two-shaft rotary safety cutter according to claim 1, wherein said safety rim is a spring.

4. The two-shaft rotary safety cutter according to claim 1, wherein said safety
10 rim is a bar.